Verified ProSafety[™]

Specialty Concrete Solutions

Material Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

| Identification

· Product identifier

· Trade name: DOT- Industrial Grade Elephant Armor Concrete Patch and Overlay

• Details of the supplier of the safety data sheet Manufacturer/Supplier:

Way To Go Holdings, INC. www.verifiedspecialityconcrete.comPO Box 853 Durham, NH 03824

· Emergency telephone number: ChemTel 1-800-255-3224

P. Hazard(s) identification

· Classification of the substance or mixture



Health hazard

May cause cancer.



Causes skin irritation.

May cause respiratory irritation.

Causes eye irritation.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Silica
Quartz (SiO2)
Hazard statements
Causes skin and eye irritation.
May cause cancer.
May cause respiratory irritation.
Precautionary statements
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Page 1/9

Reviewed on 05/16/2014

Printing date 05/21/2014

d

Verified Specialty Concrete Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Trade name: DOT- Industrial Grade Verified Specialty Concrete Patch and Overlay

Reviewed on 05/16/2014

Printing date 05/21/2014

(Contd. of page 1)

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label). Take off contaminated clothing and wash before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. Call a POISON CENTER/doctor if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: NFPA ratings (scale 0 - 4) Health = 1Fire = 0Reactivity = 0 · HMIS-ratings (scale 0 - 4)



3 Composition/information on ingredients

· Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous d 	components:	
960375-09-1	Calcium Sulfoaluminate Cement	25-50%
	1 Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
1317-95-9	Silica	25-50%
	Carc. 1A, H350; STOT SE 3, H335	
	Aluminosilicate Glass	15-35%
	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
65997-15-1	Cement, portland, chemicals	5-10%
14808-60-7	Quartz (SiO2)	≤ 2.5%
	Carc. 1A, H350; STOT RE 1, H372; Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	
* 4 First-aid m	neasures	

Description of first aid measures
 After inhalation: In case of unconsciousness, place patient securely on side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: Give large amounts of water. If symptoms persist consult doctor.

Page 2/9

Verified Seciality Concrete Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 05/16/2014

Trade name: DOT- Industrial Grade Verified Specialty Concrete Patch and Overlay Printing date 05/21/2014

(Contd. of page 2)

• Most important symptoms and effects, both acute and delayed No further relevant information available.

 Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

· Personal precautions, protective equipment and emergency procedures Not required.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling No special precautions are necessary if used correctly.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Con	trol parameters	
· Com	· Components with occupational exposure limits:	
1317	'-95-9 Silica	
PEL	see Quartz listing	
REL	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A	
TLV	TLV withdrawn	
6599	7-15-1 Cement, portland, chemicals	
PEL	Long-term value: 50 mppcf or 15* 5** mg/m ³ *total dust **respirable fraction	
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction	
	(Contd. on page 4)	

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 05/16/2014

Trade name: DOT- Industrial Grade Verified Specialty Concrete Patch and Overlay Printing date 05/21/2014

(Contd. of page 3)

	E; *as respirable fraction
1480	8-60-7 Quartz (SiQ2)

TLV Long-term value: 1* mg/m³

14808-60-7 Quartz (SiO2)

- PEL
 see Quartz listing

 REL
 Long-term value: 0.05* mg/m³

 *respirable dust; See Pocket Guide App. A
- TLV Long-term value: 0.025* mg/m³ *as respirable fraction

• Additional information: The lists that were valid during the creation were used as basis.

• Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Tightly sealed goggles

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:	
Form:	Granulate
Color:	Grey
· Odor:	Odorless
· Odor threshold:	Not determined.
· pH-value:	Not applicable.

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 05/16/2014

Trade name: DOT- Industrial Grade Verified Specialty Concrete Patch and Overlay Printing date 05/21/2014

· Change in condition Melting point/Melting range: 999 °C (1830 °F) Boiling point/Boiling range: · Flash point: Not applicable. · Flammability (solid, gaseous): Not determined. · Ignition temperature: Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. • Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Lower: Not determined. Upper: Not determined. · Vapor pressure: Not applicable. · Density: Not determined. · Relative density Not determined. · Vapour density Not applicable. · Evaporation rate Not applicable. · Solubility in / Miscibility with Water: Insoluble. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not applicable. Kinematic: Not applicable. · Solvent content: Organic solvents: 0.0 % Solids content: 98.3 % No further relevant information available. · Other information

· *Reactivity* No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

• Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

· on the eye: Irritating effect.

(Contd. of page 4)

Verified Specialty Concrete Safety Data Sheet (SDS)

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Page 6/9

Reviewed on 05/16/2014

Trade name: DOT- Industrial Grade Verified Specialty Concrete Patch and Overlay Printing date 05/21/2014

(Contd. of page 5)

- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories

 · IARC (International Agency for Research on Cancer)

 1317-95-9
 Silica

 14808-60-7
 Quartz (SiO2)

 · NTP (National Toxicology Program)
 1

 1317-95-9
 Silica

 1317-95-9
 Silica

 1317-95-9
 Silica

 14808-60-7
 Quartz (SiO2)

 · OSHA-Ca (Occupational Safety & Health Administration)

 None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · *Bioaccumulative potential* No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

- Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

3 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information

- · UN-Number
- · DOT, ADR, ADN, IMDG, IATA
- · UN proper shipping name
- · DOT, ADR, ADN, IMDG, IATA
- Transport hazard class(es)
- · DOT, ADR, ADN, IMDG, IATA · Class

Non-Regulated Material Not Regulated for Transportation Non-Regulated Material

Non-Regulated Material

Page 7/9

Reviewed on 05/16/2014

Trade name: DOT- Industrial Grade Verified Specialty Concrete Patch and Overlay Printing date 05/21/2014

· Packing group · DOT, ADR, IMDG, IATA	(Contd. of page Non-Regulated Material
Environmental hazards:	
· Marine pollutant:	No Not emplicable
 Special precautions for user Transport in bulk according to 	Not applicable.
MARPOL73/78 and the IBC Coo UN "Model Regulation":	de Not applicable.
5 Regulatory information	
· Safety, health and environmen · Sara	tal regulations/legislation specific for the substance or mixture
· Section 355 (extremely hazardo	ous substances):
None of the ingredients is listed.	
· Section 313 (Specific toxic che	mical listings):
None of the ingredients is listed.	
· TSCA (Toxic Substances Conti	rol Act):
65997-15-1 Cement, portland, cl	nemicals
7439-89-6 iron	
14808-60-7 Quartz (SiO2)	
36290-04-7 Sodium salt of poly-	naphthalene sulfonic acid
64741-89-5 Distillates (petroleur	n), solvent-refined light paraffinic
64741-88-4 Distillates (petroleur	n), solvent-refined heavy paraffinic
7757-82-6 sodium sulphate	
7732-18-5 water, distilled, cond	luctivity or of similar purity
· Proposition 65	
· Chemicals known to cause car	icer:
14808-60-7 Quartz (SiO2)	
· Chemicals known to cause rep	roductive toxicity for females:
None of the ingredients is listed.	
· Chemicals known to cause rep	roductive toxicity for males:
None of the ingredients is listed.	
· Chemicals known to cause dev	elopmental toxicity:
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protectior	ו Agency)
None of the ingredients is listed.	
· TLV (Threshold Limit Value est	tablished by ACGIH)
1317-95-9 Silica	A
14808-60-7 Quartz (SiO2)	A
NIOSH-Ca (National Institute fo	or Occupational Safety and Health)
1317-95-9 Silica	

OSHA HazCom 2012 Standard 29 CFR 1910.1200. Prepared to GHS Rev03.

Reviewed on 05/16/2014

Printing date 05/21/2014

Trade name: DOT- Industrial Verified Specialty Concrete Patch and Overlay

(Contd. of page 7)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Silica

Quartz (SiO2)

· Hazard statements

Causes skin and eye irritation. May cause cancer.

May cause respiratory irritation.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Wash thoroughly after handling.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

Take off contaminated clothing and wash before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Call a POISON CENTER/doctor if you feel unwell.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

• National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

• State Right to Know

· State Right t	lo Know	
960375-09-1	Calcium Sulfoaluminate Cement	25-50%
	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	
1317-95-9	Silica	25-50%
	🚸 Carc. 1A, H350; 🚸 STOT SE 3, H335	-
	Aluminosilicate Glass	15-35%
	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	-
65997-15-1	Cement, portland, chemicals	5-10%

(Contd. on page 9)

Reviewed on 05/16/2014

Trade name: DOT- Industrial Verified Specialty Concrete Patch and Overlay

Printing date 05/21/2014

	(Cor	ntd. of page
7439-89-6		≤ 2.5%
14808-60-7	Quartz (SiO2) Carc. 1A, H350; STOT RE 1, H372; () Acute Tox. 4, H332; STOT SE 3, H335; Eye Irrit. 2B, H320	≤ 2.5%
All ingredient	s are listed.	1
· Chemical sa	fety assessment: A Chemical Safety Assessment has not been carried out.	
6 Other info	rmation	
Date of prep Abbreviatior	uct features and shall not establish a legally valid contractual relationship. aration / last revision 05/21/2014 / 2 as and acronyms:	
Carriage of Dang	ropéen sur le transport des marchandises dangereuses par Route (European Agreement concerning the Inte gerous Goods by Road) nal Maritime Code for Dangerous Goods	ernational
IATA: Internation	ment of Transportation al Air Transport Association n Conference of Governmental Industrial Hygienists	
EINECS: Europe	an List of Notified Chemical Substances	
NFPA: National I	Abstracts Service (division of the American Chemical Society) Fire Protection Association (USA)	
Acute Tox. 4: Ac	s Materials Identification System (USA) ute toxicity, Hazard Category 4 corrosion/irritation, Hazard Category 2	
	Sonoologin Marano, evo irritation, Hazard Category 2P	

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B Carc. 1A: Carcinogenicity, Hazard Category 1A STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

• * Data compared to the previous version altered.

SDS / MSDS Created by MSDS Authoring Services (www.MSDSAuthoring.com)