



ArmourTone[®]
ABUSE RESISTANT FINISHES

ArmourSeal[™]

Description

ArmourTone Seal is a high performance epoxy-acrylic hybrid sealer that improves resistance to water, chemicals, stains, scratches and scuffs. Available in gloss and matte finish.

Uses

For interior or exterior applications over smooth or textured ArmourTone Finish surfaces and other types of plaster or wall finishes.

Packaging

8.5 lb. 1 gallon plastic jug

Color

Clear

Coverage

Approximately 700-900 square ft. per gallon (one coat). Coverage varies depending on surface conditions and thickness of application.

Shelf Life / Storage

Minimum of one year when stored in a cool, dry location out of direct sunlight and kept from freezing.

Mixing

Mix or shake ArmourSeal before use. Add up to 6 ounces clean, potable water per gallon may be added to adjust viscosity. Close container when not in use.

Substrate Preparation

Surface must be clean, dry and free of bond-inhibiting materials such as dust, dirt, rust, grease, oil, mildew, fungus, form-release agents or any other contaminants.

Limitations

- Use only on surfaces that are sound, clean, dry and free from any residue that might affect the ability of this product to bond to the surface.
- The use of a sealer is recommended in high-moisture or high traffic areas.
- Ambient and surface temperatures must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from moisture as needed.
- Application in direct sunlight in hot weather may adversely affect aesthetics.
- Do not allow to freeze until completely dry.
- Always wear proper safety equipment, including particle mask, eye protection and gloves when mixing and/or applying this product.

Application

- Periodically, as the work progresses, evaluate it from a distance to ensure the desired effect is being produced across the entire surface.
- If installing in a wet environment, the ArmourTone High Humidity Wet Areas specification must be followed.
- Apply sealer using a 3/8 nap or small foam roller.

- Load roller with product and roll off excess.
- Apply ArmourSeal to wall surface, overlapping 1-2 inches with each stroke. Back roll to avoid lap lines or drips.
- Best results are achieved by keeping a wet edge, working from corner to corner.

Drying Time

Avoid rain, heavy traffic and cleaning for 48 hours after application. Allow material to dry 3-4 hours under normal conditions. High Humidity and low temperatures extend drying time.

Clean Up

Clean tools frequently using clean water prior to sealer drying.

Composition

VOC content: <12 grams per liter

First Aid

SKIN CONTACT: Wash thoroughly with soap and water.

EYE CONTACT: Flush immediately with water for 10-15 minutes and contact a physician..

Spills:

Wipe up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

8.5 lbs. • 3.86 kg.

ArmourTone Finishes LLC

12600 Osito Court NE • Albuquerque, NM 87111 • (505) 400-7166