



ArmourTone Top Coat

Description

ArmourTone Top Coat is a high performance epoxy-acrylic hybrid sealer that is trowel or blade applied. Top Coat improves resistance to water, chemicals, stains, scratches and scuffs. Available in gloss and satin finishes.

Uses

For interior or exterior applications over smooth surfaces. Use Top Coat to seal any smooth ArmourTone Finish or other types of plaster or wall finishes.

Packaging

8 lb. Pail or 1 gallon plastic jug

Color

Clear

Coverage

Approximately 400– 600 square ft per gallon (one coat). Coverage varies depending on surface conditions and thickness of application.

Shelf Life / Storage

Minimum of one year when stored in a cool, dry location out of direct sunlight and kept from freezing.

Mixing

No mixing or thinning of the product is required.

Substrate Preparation

Surface must be clean, dry and free of bond-inhibiting materials such as such as dust, dirt, rust, grease, oil, mildew, fungus, form-release agents or any other contaminants.

Limitations

- Use only on surfaces that are sound, clean, dry and free from

any residue that might affect the ability of this product to bond to the surface.

- The use of a sealer is recommended in high-moisture or high traffic areas.
- Ambient and surface temperatures must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from moisture as needed.
- Application in direct sunlight in hot weather may adversely affect aesthetics.
- Do not allow to freeze until completely dry.
- Always wear proper safety equipment, including particle mask, eye protection and gloves when mixing and/or applying this product.

Application

- Periodically, as the work progresses, evaluate it from a distance to ensure the desired effect is being produced across the entire surface.
- If installing in a wet environment, the Variance High Humidity Wet Areas specification must be followed.
- Apply a test area in an inconspicuous area to evaluate compatibility.
- Top Coat may be applied over any smooth ArmourTone finish.
- For best results, apply using Venetian trowels or bondo blades
- Apply Top Coat in very thin, even coats.
- Apply using decorative, multi-directional trowel strokes.
- For maximum protection and for a more even appearance apply

2 or more coats.

- Allow 2 hours in between coats. Once the surface has dried to the touch it may be burnished slightly with a clean, dry Venetian trowel to increase sheen and smoothness.

Drying Time

Avoid rain, heavy traffic and cleaning for 48 hours after application. Allow material to try 3-4 hours under normal conditions. High Humidity and low temperatures extend drying time.

Clean Up

Clean tools frequently using clean water prior to drying

First Aid

SKIN CONTACT: Wash thoroughly with soap and water.
EYE CONTACT: Flush immediately with water for 10-15 minutes and contact a physician..



Armourtone Finishes, LLC
12600 Osito Court NE
Albuquerque, NM 87111

For sales or distribution information, please contact
Rob Knight: (505) 400-7166

For product and application questions, please contact
Danny Carrillo: (505) 382-0905



Spills:

Wipe up and wash with water immediately. If material has set, scrape material with appropriate tools and clean with citric acid.

Disposal:

Dispose of in accordance of local, state or federal regulations.

Warning:

KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION, FOR INDUSTRIAL USE ONLY.

Last Revised 12-17



Armourtone Finishes, LLC
12600 Osito Court NE
Albuquerque, NM 87111

For sales or distribution information, please contact
Rob Knight: (505) 400-7166

For product and application questions, please contact
Danny Carrillo: (505) 382-0905